

Material Specification:


NO.	Parts	Materials	Re-mark
1	HANDWHEEL NUT	SS400 Zn. Plating	
2	NAME PLATE	A1050P	
3	HANDWHEEL	ADC12	
4	STEM	SUS 410	HB 200 Max
5	PACKING NUT	FCD450-10	
6	GLAND	SUS 410	HB 200 Max
7	PACKING	GRAPHITE	
8	BONNET	FCD450-10	
9	BODY	FCD450-10	
10	DISC	SCS 1	HRC 34~43
11	BODY SEAT RING	SUS 410	HB 200 Max

Features

- Rising Stem
- Screwed Bonnet
- Solid Wedge Disc
- Flanged Ends
- Graphite Packing
- Stainless Steel Stem, Disc and Seat Ring
- JV 4-2

RATING	
120°C STATIC WATER	14kgf/cm <sup>2</sup>
220°C STEAM, AIR, GAS, OIL SHOCK WATER	10kgf/cm <sup>2</sup>


PRESSURE TEST	
SHELL	HYD. 21kgf/cm <sup>2</sup>
SEAT	AIR 6kgf/cm <sup>2</sup>

SIDE	OTHER SIDE	
DI	"10K-mm SIZE"	
		
閥體標示 BODY MARKING		

詳細尺寸 Dimension

單位 Unit: 公釐 mm

規格	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
L	90	100	110	120	130	140
H	153	176	203	238	278	319
h	135	153	170	200	232	264
øD	95	100	125	135	140	155
W	70	80	90	100	125	140

圖號	JIS-10K 球狀石墨鑄鐵閘門閥(昇桿式)	
F45D	JIS10K Ductile Iron Gate Valve(Rising Stem)	
繪圖 陳明啓	107.05.08	比 例 —— 角 法 第三角 單 位 mm
設計 賴金輝	107.05.08	
審核 許進春	107.05.08	
姓名 日期		 金口金屬股份有限公司

符號位置原有尺寸更改尺寸更改者審核日期